



ML Industries, Inc.

850 Purchase Order

Document Control

Version

2017.11.26.1

Document History

Version	Release Date	Effective Date	Author
2017.11.26.1	11/26/2017	In Use	M.O.
2017.11.26.1 Creation of Document			

Table of Contents

850	Purchase Order.....	1
ISA	Interchange Control Header	3
GS	Functional Group Header	5
ST	Transaction Set Header	7
BEG	Beginning Segment for Purchase Order.....	8
CUR	Currency.....	10
REF	Reference Identification	11
PER	Administrative Communications Contact.....	12
DTM	Date/Time Reference	13
TD5	Carrier Details (Routing Sequence/Transit Time)	14
MAN	Marks and Numbers	15
N1	Loop Name.....	16
N1	Name.....	17
N2	Additional Name Information	18
N3	Address Information	19
N4	Geographic Location	20
PO1	Loop Baseline Item Data	21
PO1	Baseline Item Data	22
PID	Loop Product/Item Description	24
PID	Product/Item Description	25
REF	Reference Identification	26
SAC	Loop Service, Promotion, Allowance, or Charge Information.....	27
SAC	Service, Promotion, Allowance, or Charge Information	28
DTM	Date/Time Reference	30
MAN	Marks and Numbers	31
SCH	Loop Line Item Schedule	32
SCH	Line Item Schedule.....	33
CTT	Loop Transaction Totals	34
CTT	Transaction Totals	35
AMT	Monetary Amount	36
SE	Transaction Set Trailer	37
GE	Functional Group Trailer.....	38
IEA	Interchange Control Trailer	39

850

Purchase Order

Functional Group=PO

Purpose: This document contains the standard for all customers when implementing the EDI 850 Purchase Order

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BEG	Beginning Segment for Purchase Order	M	1			Must use
040	CUR	Currency	O	1			Not used
050	REF	Reference Identification	O	>1			Used
060	PER	Administrative Communications Contact	O	3			Not used
150	DTM	Date/Time Reference	O	10			Used
240	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12			Used
270	MAN	Marks and Numbers	O	10			Used
LOOP ID - N1					200		
310	N1	Name	O	1			Used
320	N2	Additional Name Information	O	2			Used
330	N3	Address Information	O	2			Used
340	N4	Geographic Location	O	>1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - PO1					100000	N2/010L	
010	PO1	Baseline Item Data	M	1		N2/010	Must use
LOOP ID - PID					1000		
050	PID	Product/Item Description	O	1			Used
100	REF	Reference Identification	O	>1			Used
LOOP ID - SAC					25		
130	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used
210	DTM	Date/Time Reference	O	10			Not used
280	MAN	Marks and Numbers	O	10			Used
LOOP ID - SCH					200	N2/295L	
295	SCH	Line Item Schedule	O	1		N2/295	Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - CTT					1	N3/010L	
010	CTT	Transaction Totals	O	1		N3/010	Used
020	AMT	Monetary Amount	O	1		N3/020	Used
030	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

- 2/010L PO102 is required.
- 2/010 PO102 is required.
- 2/295L The SCH segment is used to specify various quantities of items ordered that are to be scheduled. When this segment is used the unit of measurement code (SCH02) should always be identical to the unit of measurement code in the associated PO1 segment (PO103) and the sum of values of quantity (SCH01) should always equal the quantity ordered (PO102) in the PO1 segment.
- 2/295 The SCH segment is used to specify various quantities of items ordered that are to be scheduled. When this segment is used the unit of measurement code (SCH02) should always be identical to the unit of measurement code in the associated PO1 segment (PO103) and the sum of values of quantity (SCH01) should always equal the quantity ordered (PO102) in the PO1 segment.
- 3/010L The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.
- 3/010 The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.
- 3/020 If AMT is used in the summary area, then AMT01 will = TT and AMT02 will indicate total transaction amount as calculated by the sender.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
		Description: Code to identify the type of information in the Authorization Information				
		<u>Code</u>		<u>Name</u>		
		00		No Authorization Information Present (No Meaningful Information in I02)		
ISA02	I02	Authorization Information	M	AN	10/10	Must use
		Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)				
		Must be Spaces				
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
		Description: Code to identify the type of information in the Security Information				
		<u>Code</u>		<u>Name</u>		
		00		No Security Information Present (No Meaningful Information in I04)		
ISA04	I04	Security Information	M	AN	10/10	Must use
		Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)				
		* Must be Spaces *				
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
		Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified				
		All valid standard codes are used.				
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
		Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified				
		<u>Code</u>		<u>Name</u>		
		01		Duns (Dun & Bradstreet)		
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
		Description: MLI Receiver ID - 340961012				
ISA09	I08	Interchange Date	M	DT	6/6	Must use
		Description: Date of the interchange				
ISA10	I09	Interchange Time	M	TM	4/4	Must use
		Description: Time of the interchange				

ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use
Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used.						
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
Description: Code specifying the version number of the interchange control segments						
		<u>Code</u>	<u>Name</u>			
		00401	Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997			
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
Description: Code sent by the sender to request an interchange acknowledgment (TA1)						
		<u>Code</u>	<u>Name</u>			
		0	No Acknowledgment Requested			
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information						
		<u>Code</u>	<u>Name</u>			
		P	Production Data			
		T	Test Data			
ISA16	I15	Component Element Separator	M		1/1	Must use
Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator						

* Must use > *

Comments:

1. Example:
ISA*00* *00* *01*123456789 *01*340961012 *080807*0830*U*00401*000000001*0*P*>~

GS

Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use
Description: Code identifying a group of application related transaction sets						
		<u>Code</u>	<u>Name</u>			
		PO	Purchase Order (850)			
GS02	142	Application Sender's Code	M	AN	2/15	Must use
Description: Code identifying party sending transmission; codes agreed to by trading partners						
GS03	124	Application Receiver's Code	M	AN	2/15	Must use
Description: MLI receiver ID - 340961012						
GS04	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD						
GS05	337	Time	M	TM	4/8	Must use
Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)						
GS06	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						
GS07	455	Responsible Agency Code	M	ID	1/2	Must use
Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480						
		<u>Code</u>	<u>Name</u>			
		X	Accredited Standards Committee X12			
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed						
		<u>Code</u>	<u>Name</u>			
		004010	Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997			

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. Example: GS*PO*123456789*340961012*20080807*0830*1*X*004010~

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use
Description: Code uniquely identifying a Transaction Set						
		<u>Code</u>		<u>Name</u>		
		850		Purchase Order		
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Comments:

1. Example: ST*850*000000001~

BEG Beginning Segment for Purchase Order

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 12

User Option (Usage): Must use

Purpose: To indicate the beginning of the Purchase Order Transaction Set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BEG01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
		Description: Code identifying purpose of transaction set				
		<u>Code</u>		<u>Name</u>		
		00		Original		
BEG02	92	Purchase Order Type Code	M	ID	2/2	Must use
		Description: Code specifying the type of Purchase Order				
		<u>Code</u>		<u>Name</u>		
		DS		Dropship		
		EO		Emergency Order		
		NE		New Order		
		RO		Rush Order		
BEG03	324	Purchase Order Number	M	AN	1/22	Must use
		Description: Identifying number for Purchase Order assigned by the orderer/purchaser				
BEG04	328	Release Number	O	AN	1/30	Not used
		Description: Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction				
BEG05	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BEG06	367	Contract Number	O	AN	1/30	Used
		Description: Contract number				
BEG07	587	Acknowledgment Type	O	ID	2/2	Used
		Description: Code specifying the type of acknowledgment All valid standard codes are used.				
BEG08	1019	Invoice Type Code	O	ID	3/3	Used
		Description: Code defining the method by which invoices are to be processed All valid standard codes are used.				
BEG09	1166	Contract Type Code	O	ID	2/2	Used
		Description: Code identifying a contract type All valid standard codes are used.				
BEG10	1232	Purchase Category	O	ID	2/2	Used
		Description: Code identifying the broad category of products or services being acquired All valid standard codes are used.				
BEG11	786	Security Level Code	O	ID	2/2	Used
		Description: Code indicating the level of confidentiality assigned by the sender to the information following				

All valid standard codes are used.

BEG12 640 **Transaction Type Code** O ID 2/2 Used

Description: Code specifying the type of transaction
All valid standard codes are used.

Semantics:

- 1. BEG05 is the date assigned by the purchaser to purchase order.

Comments:

- 1. Example: BEG*00*NE*123456*20080807*123456789~

CUR Currency

Pos: 040	Max: 1
Heading - Optional	
Loop: N/A	Elements: 5

User Option (Usage): Not used

Purpose: To specify the currency (dollars, pounds, francs, etc.) used in a transaction

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CUR01	98	Entity Identifier Code	M	ID	2/3	Not used
		Description: Code identifying an organizational entity, a physical location, property or an individual All valid standard codes are used.				
CUR02	100	Currency Code	M	ID	3/3	Must use
		Description: Code (Standard ISO) for country in whose currency the charges are specified				
CUR03	280	Exchange Rate	O	R	4/10	Used
		Description: Value to be used as a multiplier conversion factor to convert monetary value from one currency to another				
CUR04	98	Entity Identifier Code	O	ID	2/3	Used
		Description: Code identifying an organizational entity, a physical location, property or an individual All valid standard codes are used.				
CUR05	100	Currency Code	O	ID	3/3	Used
		Description: Code (Standard ISO) for country in whose currency the charges are specified				

Syntax Rules:

1. C0807 - If CUR08 is present, then CUR07 is required.
2. C0907 - If CUR09 is present, then CUR07 is required.
3. L101112 - If CUR10 is present, then at least one of CUR11 or CUR12 is required.
4. C1110 - If CUR11 is present, then CUR10 is required.
5. C1210 - If CUR12 is present, then CUR10 is required.
6. L131415 - If CUR13 is present, then at least one of CUR14 or CUR15 is required.
7. C1413 - If CUR14 is present, then CUR13 is required.
8. C1513 - If CUR15 is present, then CUR13 is required.
9. L161718 - If CUR16 is present, then at least one of CUR17 or CUR18 is required.
10. C1716 - If CUR17 is present, then CUR16 is required.
11. C1816 - If CUR18 is present, then CUR16 is required.
12. L192021 - If CUR19 is present, then at least one of CUR20 or CUR21 is required.
13. C2019 - If CUR20 is present, then CUR19 is required.
14. C2119 - If CUR21 is present, then CUR19 is required.

Comments:

1. See Figures Appendix for examples detailing the use of the CUR segment.

REF Reference Identification

Pos: 050	Max: >1
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

<u>Code</u>	<u>Name</u>
CO	Customer Order Number
DG	Drawing Number
PD	Promotion/Deal Number
PR	Price Quote Number

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

PER Administrative Communications Contact

Pos: 060	Max: 3
Heading - Optional	
Loop: N/A	Elements: 6

User Option (Usage): Not used

Purpose: To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Must use
		Description: Code identifying the major duty or responsibility of the person or group named All valid standard codes are used.				
PER02	93	Name	O	AN	1/60	Used
		Description: Free-form name				
PER03	365	Communication Number Qualifier	X	ID	2/2	Used
		Description: Code identifying the type of communication number All valid standard codes are used.				
PER04	364	Communication Number	X	AN	1/80	Used
		Description: Complete communications number including country or area code when applicable				
PER05	365	Communication Number Qualifier	X	ID	2/2	Used
		Description: Code identifying the type of communication number All valid standard codes are used.				
PER06	364	Communication Number	X	AN	1/80	Used
		Description: Complete communications number including country or area code when applicable				

Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

DTM Date/Time Reference

Pos: 150	Max: 10
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use
		Description: Code specifying type of date or time, or both date and time				
		<u>Code</u>		<u>Name</u>		
		002		Delivery Requested		
		037		Ship Not Before		
		038		Ship No Later		
DTM02	373	Date	X	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 240	Max: 12
Heading - Optional	
Loop: N/A	Elements: 5

User Option (Usage): Used

Purpose: To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD501	133	Routing Sequence Code	O	ID	1/2	Not used
		Description: Code describing the relationship of a carrier to a specific shipment movement All valid standard codes are used.				
TD502	66	Identification Code Qualifier	X	ID	1/2	Used
		Description: Code designating the system/method of code structure used for Identification Code (67)				
		<u>Code</u>		<u>Name</u>		
		2		Standard Carrier Alpha Code (SCAC)		
TD503	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
		*Carrier SCAC Code *				
TD504	91	Transportation Method/Type Code	X	ID	1/2	Used
		Description: Code specifying the method or type of transportation for the shipment All valid standard codes are used.				
TD505	387	Routing	X	AN	1/35	Used
		Description: Free-form description of the routing or requested routing for shipment, or the originating carrier's identity				

Syntax Rules:

1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
2. C0203 - If TD502 is present, then TD503 is required.
3. C0708 - If TD507 is present, then TD508 is required.
4. C1011 - If TD510 is present, then TD511 is required.
5. C1312 - If TD513 is present, then TD512 is required.
6. C1413 - If TD514 is present, then TD513 is required.
7. C1512 - If TD515 is present, then TD512 is required.

Semantics:

1. TD515 is the country where the service is to be performed.

Comments:

1. When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

MAN Marks and Numbers

Pos: 270	Max: 10
Heading - Optional	
Loop: N/A	Elements: 6

User Option (Usage): Used

Purpose: To indicate identifying marks and numbers for shipping containers

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Used
		Description: Code specifying the application or source of Marks and Numbers (87) All valid standard codes are used.				
MAN02	87	Marks and Numbers	M	AN	1/48	Used
		Description: Marks and numbers used to identify a shipment or parts of a shipment				
MAN03	87	Marks and Numbers	O	AN	1/48	Not used
		Description: Marks and numbers used to identify a shipment or parts of a shipment				
MAN04	88	Marks and Numbers Qualifier	X	ID	1/2	Not used
		Description: Code specifying the application or source of Marks and Numbers (87) All valid standard codes are used.				
MAN05	87	Marks and Numbers	X	AN	1/48	Not used
		Description: Marks and numbers used to identify a shipment or parts of a shipment				
MAN06	87	Marks and Numbers	O	AN	1/48	Not used
		Description: Marks and numbers used to identify a shipment or parts of a shipment				

Syntax Rules:

1. P0405 - If either MAN04 or MAN05 is present, then the other is required.
2. C0605 - If MAN06 is present, then MAN05 is required.

Semantics:

1. MAN01/MAN02 and MAN04/MAN05 may be used to identify two different marks and numbers assigned to the same physical container.
2. When both MAN02 and MAN03 are used, MAN02 is the starting number of a sequential range and MAN03 is the ending number of that range.
3. When both MAN05 and MAN06 are used, MAN05 is the starting number of a sequential range, and MAN06 is the ending number of that range.

Comments:

1. When MAN01 contains code "UC" (U.P.C. Shipping Container Code) and MAN05/MAN06 contain a range of ID numbers, MAN03 is not used. The reason for this is that the U.P.C. Shipping Container code is the same on every carton that is represented in the range in MAN05/MAN06.
2. MAN03 and/or MAN06 are only used when sending a range(s) of ID numbers.
3. When both MAN02/MAN03 and MAN05/MAN06 are used to send ranges of ID numbers, the integrity of the two ID numbers must be maintained.

Loop Name

Pos: 310	Repeat: 200
	Optional
Loop: N1	Elements: N/A

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
310	N1	Name	O	1		Used
320	N2	Additional Name Information	O	2		Used
330	N3	Address Information	O	2		Used
340	N4	Geographic Location	O	>1		Used

N1

Name

Pos: 310	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
		<u>Code</u>	<u>Name</u>			
		BS	Bill and Ship To			
		BT	Bill-to-Party			
		BY	Buying Party (Purchaser)			
		EN	End User			
		SE	Selling Party			
		ST	Ship To			
N102	93	Name	X	AN	1/60	Must use
Description: Free-form name						
N103	66	Identification Code Qualifier	X	ID	1/2	Must use
Description: Code designating the system/method of code structure used for Identification Code (67)						
All valid standard codes are used.						
N104	67	Identification Code	X	AN	2/80	Must use
Description: Code identifying a party or other code. MLI requires a branch number here.						

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N2 Additional Name Information

Pos: 320	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

Purpose: To specify additional names or those longer than 35 characters in length

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/60	Must use
		Description: Free-form name				
N202	93	Name	O	AN	1/60	Used
		Description: Free-form name				

N3

Address Information

Pos: 330	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4

Geographic Location

Pos: 340	Max: >1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Used
		Description: Code identifying the country				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop Baseline Item Data

Pos: 010	Repeat: 100000
Mandatory	
Loop: PO1	Elements: N/A

User Option (Usage): Must use

Purpose: To specify basic and most frequently used line item data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	PO1	Baseline Item Data	M	1		Must use
050		Loop PID	O		1000	Used
100	REF	Reference Identification	O	>1		Used
130		Loop SAC	O		25	Used
210	DTM	Date/Time Reference	O	10		Not used
280	MAN	Marks and Numbers	O	10		Used
295		Loop SCH	O		200	Used

PO1 Baseline Item Data

Pos: 010	Max: 1
Detail - Mandatory	
Loop: PO1	Elements: 14

User Option (Usage): Must use

Purpose: To specify basic and most frequently used line item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO101	350	Assigned Identification	O	AN	1/20	Used
		Description: Alphanumeric characters assigned for differentiation within a transaction set				
PO102	330	Quantity Ordered	X	R	1/15	Must use
		Description: Quantity ordered				
PO103	355	Unit or Basis for Measurement Code	O	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		<u>Code</u>		<u>Name</u>		
		EA		Each		
PO104	212	Unit Price	X	R	1/17	Used
		Description: Price per unit of product, service, commodity, etc.				
PO105	639	Basis of Unit Price Code	O	ID	2/2	Used
		Description: Code identifying the type of unit price for an item				
		<u>Code</u>		<u>Name</u>		
		HP		Price per Hundred		
		NC		No Charge		
		PE		Price per Each		
		PF		Price Per Foot		
		PP		Price per Pound		
PO106	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		<u>Code</u>		<u>Name</u>		
		BP		Buyer's Part Number		
		UI		U.P.C. Consumer Package Code (1-5-5)		
		UP		U.P.C. Consumer Package Code (1-5-5-1)		
		VC		Vendor's (Seller's) Catalog Number		
		VP		Vendor's (Seller's) Part Number		
PO107	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
PO108	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		All valid standard codes are used.				
PO109	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
PO110	235	Product/Service ID Qualifier	X	ID	2/2	Used

		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) All valid standard codes are used.				
PO111	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
PO112	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) All valid standard codes are used.				
PO113	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
PO114	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) All valid standard codes are used.				

Syntax Rules:

1. C0302 - If PO103 is present, then PO102 is required.
2. C0504 - If PO105 is present, then PO104 is required.
3. P0607 - If either PO106 or PO107 is present, then the other is required.
4. P0809 - If either PO108 or PO109 is present, then the other is required.
5. P1011 - If either PO110 or PO111 is present, then the other is required.
6. P1213 - If either PO112 or PO113 is present, then the other is required.
7. P1415 - If either PO114 or PO115 is present, then the other is required.
8. P1617 - If either PO116 or PO117 is present, then the other is required.
9. P1819 - If either PO118 or PO119 is present, then the other is required.
10. P2021 - If either PO120 or PO121 is present, then the other is required.
11. P2223 - If either PO122 or PO123 is present, then the other is required.
12. P2425 - If either PO124 or PO125 is present, then the other is required.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. PO101 is the line item identification.
3. PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Loop Product/Item Description

Pos: 050	Repeat: 1000
	Optional
Loop: PID	Elements: N/A

User Option (Usage): Used

Purpose: To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
050	PID	Product/Item Description	O	1		Used

PID

Product/Item Description

Pos: 050	Max: 1
Detail - Optional	
Loop: PID	Elements: 5

User Option (Usage): Used

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use
		Description: Code indicating the format of a description All valid standard codes are used.				
PID02	750	Product/Process Characteristic Code	O	ID	2/3	Not used
		Description: Code identifying the general class of a product or process characteristic All valid standard codes are used.				
PID03	559	Agency Qualifier Code	X	ID	2/2	Not used
		Description: Code identifying the agency assigning the code values All valid standard codes are used.				
PID04	751	Product Description Code	X	AN	1/12	Not used
		Description: A code from an industry code list which provides specific data about a product characteristic				
PID05	352	Description	X	AN	1/80	Used
		Description: A free-form description to clarify the related data elements and their content				

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

REF Reference Identification

Pos: 100	Max: >1
Detail - Optional	
Loop: PO1	Elements: 3

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use
		Description: Code qualifying the Reference Identification				
		<u>Code</u>		<u>Name</u>		
		PR		Price Quote Number		
REF02	127	Reference Identification	X	AN	1/30	Used
		Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
REF03	352	Description	X	AN	1/80	Not used
		Description: A free-form description to clarify the related data elements and their content				

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Service, Promotion, Allowance, or Charge Information

Pos: 130	Repeat: 25
	Optional
Loop: SAC	Elements: N/A

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
130	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

SAC Service, Promotion, Allowance, or Charge Information

Pos: 130	Max: 1
Detail - Optional	
Loop: SAC	Elements: 5

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use
		Description: Code which indicates an allowance or charge for the service specified All valid standard codes are used.				
SAC02	1300	Service, Promotion, Allowance, or Charge Code	X	ID	4/4	Used
		Description: Code identifying the service, promotion, allowance, or charge All valid standard codes are used.				
SAC03	559	Agency Qualifier Code	X	ID	2/2	Used
		Description: Code identifying the agency assigning the code values All valid standard codes are used.				
SAC04	1301	Agency Service, Promotion, Allowance, or Charge Code	X	AN	1/10	Used
		Description: Agency maintained code identifying the service, promotion, allowance, or charge				
SAC05	610	Amount	O	N2	1/15	Used
		Description: Monetary amount				

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.
5. C1110 - If SAC11 is present, then SAC10 is required.
6. L130204 - If SAC13 is present, then at least one of SAC02 or SAC04 is required.
7. C1413 - If SAC14 is present, then SAC13 is required.
8. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable to service, promotion, allowance, or charge.
7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.

8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the

promotion.

9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction to further the code in SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

DTM Date/Time Reference

Pos: 210	Max: 10
Detail - Optional	
Loop: PO1	Elements: 2

User Option (Usage): Not used

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use
Description: Code specifying type of date or time, or both date and time All valid standard codes are used.						
DTM02	373	Date	X	DT	8/8	Used
Description: Date expressed as CCYYMMDD						

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

MAN Marks and Numbers

Pos: 280	Max: 10
Detail - Optional	
Loop: PO1	Elements: 2

User Option (Usage): Used

Purpose: To indicate identifying marks and numbers for shipping containers

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Must use

Description: Code specifying the application or source of Marks and Numbers (87)
All valid standard codes are used.

MAN02	87	Marks and Numbers	M	AN	1/48	Must use
-------	----	-------------------	---	----	------	----------

Description: Marks and numbers used to identify a shipment or parts of a shipment

Syntax Rules:

1. P0405 - If either MAN04 or MAN05 is present, then the other is required.
2. C0605 - If MAN06 is present, then MAN05 is required.

Semantics:

1. MAN01/MAN02 and MAN04/MAN05 may be used to identify two different marks and numbers assigned to the same physical container.
2. When both MAN02 and MAN03 are used, MAN02 is the starting number of a sequential range and MAN03 is the ending number of that range.
3. When both MAN05 and MAN06 are used, MAN05 is the starting number of a sequential range, and MAN06 is the ending number of that range.

Comments:

1. When MAN01 contains code "UC" (U.P.C. Shipping Container Code) and MAN05/MAN06 contain a range of ID numbers, MAN03 is not used. The reason for this is that the U.P.C. Shipping Container code is the same on every carton that is represented in the range in MAN05/MAN06.
2. MAN03 and/or MAN06 are only used when sending a range(s) of ID numbers.
3. When both MAN02/MAN03 and MAN05/MAN06 are used to send ranges of ID numbers, the integrity of the two ID numbers must be maintained.

Loop Line Item Schedule

Pos: 295	Repeat: 200
	Optional
Loop: SCH	Elements: N/A

User Option (Usage): Used
Purpose: To specify the data for scheduling a specific line-item

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
295	SCH	Line Item Schedule	O	1		Used

SCH Line Item Schedule

Pos: 295	Max: 1
Detail - Optional	
Loop: SCH	Elements: 6

User Option (Usage): Used

Purpose: To specify the data for scheduling a specific line-item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SCH01	380	Quantity	M	R	1/15	Must use
		Description: Numeric value of quantity				
SCH02	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.				
SCH03	98	Entity Identifier Code	O	ID	2/3	Used
		Description: Code identifying an organizational entity, a physical location, property or an individual All valid standard codes are used.				
SCH04	93	Name	X	AN	1/60	Used
		Description: Free-form name				
SCH05	374	Date/Time Qualifier	M	ID	3/3	Must use
		Description: Code specifying type of date or time, or both date and time All valid standard codes are used.				
SCH06	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				

Syntax Rules:

1. C0304 - If SCH03 is present, then SCH04 is required.
2. L080910 - If SCH08 is present, then at least one of SCH09 or SCH10 is required.
3. C0908 - If SCH09 is present, then SCH08 is required.
4. C1008 - If SCH10 is present, then SCH08 is required.

Semantics:

1. SCH12 is the schedule identification.

Comments:

1. SCH05 specifies the interpretation to be used for SCH06 and SCH07.

Loop Transaction Totals

Pos: 010	Repeat: 1
	Mandatory
Loop: CTT	Elements: N/A

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		Used
020	AMT	Monetary Amount	O	1		Used

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: CTT	Elements: 2

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

CTT02	347	Hash Total	O	R	1/10	Used
-------	-----	-------------------	---	---	------	------

Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

AMT Monetary Amount

User Option (Usage): Used
Purpose: To indicate the total monetary amount

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AMT01	522	Amount Qualifier Code Description: Code to qualify amount All valid standard codes are used.	M	ID	1/3	Must use
AMT02	782	Monetary Amount Description: Monetary amount	M	R	1/18	Must use
AMT03	478	Credit/Debit Flag Code Description: Code indicating whether amount is a credit or debit All valid standard codes are used.	O	ID	1/1	Used

SE Transaction Set Trailer

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.

GE Functional Group Trailer

User Option (Usage): Must use

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
		Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element				
GE02	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA

Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						

New Order Example ST*850*0001~

BEG*00*NE*1234567890**20080827~
REF*VR*2046159~
PER*BD*MARY JANE WATSON*TE*800-555 -1234*FX*800 -555-5678~
N1*ST*MARVEL STUDIOS*92*SPID~
PO1*00010*50*EA*47.06*HP*VC*CATCR50*UI*78285659766~
PID*F***CABLE RETAINER CLIP PLASTIC~
DTM*106*20080903~
PO1*00020*200*EA*427.01*HP*VC*512*UI*78285667751~
PID*F***T-BAR BOX HANGER~
DTM*106*20080903~
PO1*00030*200*EA*102.17*HP*VC*MPLS*UI*78285648635~
PID*F***DRYWALL BRACKET~
DTM*106*20080903~
PO1*00040*560*EA*244.18*HP*VC*CAT324Z34*UI*78285630260~
PID*F***PRE -RIV ASSMBY~
DTM*106*20080903~
PO1*00050*50*EA*360.04*HP*VC*CAT64*UI*78285638353~
PID*F***4IN J-HOOK~
DTM*106*20080903~
CTT*5*1060~
SE*22*0001~

Drop Ship Example ST*850*0001~

BEG*00*DS*123456789**20080828~
REF*VR*2116159~
PER*BD*GWEN STACEY*TE*800-555 -1452*FX*800 -555-7269~
MAN*ZZ*EDDIE BROCK 8/27/08~
N9*ZZ*HEADER MESSAGE TEXT~
MSG*1. CONFIRM RECEIPT OF ORDER.~ MSG*2.
MATERIAL STOCK AT FACTORY.~ MSG*3.
PLEASE HAVE SHIPPED IMMEDIATELY.~ MSG*4.
ADVISE OF ANY ISSUES OR DELAYS.~
MSG*THANKS, HARRY OSBORN~
N1*BT*MARVEL STUDIOS~
N3*9242 BEVERLY BOULEVARD~
N4*BEVERLY HILLS*CA*90210~
N1*ST*THE DAILY BUGLE~
N2**ATTN: J. JONAH JAMISON / 800-555-6451~
N3*123 MAIN ST~
N4*NEW YORK*NY*10019~
N1*BY* MARVEL STUDIOS *92*SPIDL~
PO1*00010*3*EA*15.39*PE*VC*MC25X3KIT*UI*78285656654~
PID*F***KIT BAFFLE COVER 2.5X3~
DTM*106*20080829~
PO1*00020*3*EA*17.06*PE*VC*MC3X3KIT*UI*78285656655~
PID*F***KIT BAFFLE COVER 3X3~
DTM*106*20080829~
PO1*00030*3*EA*27.64*PE*VC*MC4X4KIT*UI*78285656656~
PID*F***KIT BAFFLE COVER 4X4~
DTM*106*20080829~
CTT*3*9~
SE*30*0001~